



BALANCES CENT - SERIES



Functions

- LCD display with small decimal digits
- Membrane keyboard solvent proof; easy to use with TARE, ON/OFF, PRINT and MODE keys
- Indication of the reached stable weight
- Bar-graph indicator of the remaining capacity of the balance even after the zero taring over the whole range
- Weighing underneath the balance (for models 10000 and 10000HR only on request)
- Parameters configurable by menu: reading in g (grams), lb (pound), oz (ounce), ct (carats), pcs (pieces), % (percentage).



Model Cent 203
with draft cage

Technical specifications

- Data output: RS232 I/O baud rate and parity adjustable
- Operating temperature: 10° ÷ 40°C (optimum 15° ÷ 30°C)
- Power supply: from 100 to 240VAC
- Power consumption: 200 mA
- Dimensions (WxDxH): 215x355x110mm
- Net weight: 5,2 kg

On request

- Solids density measuring devices
- Remote command to activate various signals: print, tare, etc.
- Executions with special capacity

Model	Capacity g	Readability g	Linearity g	Repeatability g	Pan mm	Calibration with mass
Cent 203	210	0,001	± 0.002	± 0.001	Ø 110	External
Cent 2000	2200	0,01	± 0.01	± 0.01	160 x 160	External
Cent 2000 CAL	2200	0,01	± 0.01	± 0.01	160 x 160	Internal
Cent 2000 CE	2200	0,01	± 0.01	± 0.01	160 x 160	Internal
Cent 4000	4200	0,01	± 0.01	± 0.01	160 x 160	Internal
Cent 4000 CAL	4200	0,01	± 0.01	± 0.01	160 x 160	Internal
Cent 4000 CE	4200	0,01	± 0.01	± 0.01	160 x 160	Internal
Cent 6000	6300	0,1	± 0.1	± 0.05	Ø 190	External
Cent 6000 CAL	6300	0,1	± 0.1	± 0.05	Ø 190	Internal
Cent 6000 CE	6300	0,1	± 0.1	± 0.05	Ø 190	Internal
Cent 6000 HR	6300	0,01	± 0.02	± 0.01	Ø 190	External
Cent 10000	10200	0,1	± 0.1	± 0.05	Ø 190	External
Cent 10000 HR	10200	0,01	± 0.05	± 0.02	Ø 190	External